

# Rackmount Monitors



Model Name	RMM-1210	RMM-1510	RMM-1511	RMM-1512	RMM-1710	RMM-1910
Picture						
Viewable Size Image	12.1"	15"	15"	15"	17"	19"
Size	6U	7U	7U	7U	9U	9U
Active Display Area(mm)	246.0(H)x184.5(V)	304.128(H)x228.096(V)	304.1(H)x228.1(V)	304.128(H)x228.096(V)	337.92(H)x270.34(V)	376.32(H)x301.056(V)
Pixel Pitch(mm)	0.3075(H)x0.3075(V)(typ.)	0.297(H)x0.297(V)	0.297(H)x0.297(V)	0.297(H)x0.297(V)	0.264(H)x0.264(V)	0.294(H)x0.294(V)
Number of Pixels	800x600	1024x768	1024x768	1024x768	1280x1024	1280x1024
Contrast Ratio	500:1(typ.)	400:1(typ.)	500:1(typ.)	400:1(typ.)	500:1(typ.)	1000:1(typ.)
Display Colour	262,144(6bit/colours)	262,144(6bit/colours)	16.2M(6bit+FRC)	16.7M (8bit/colours)	16.2M(6bit+FRC)	16.7M(8bit/colours)
Brightness(cd/m )	350	500	250(typ.)	250(typ.)	300(typ.)	250
Viewing Angle(CR>=10)	-65~65(H);-75~45(V)(typ.)	-70~70(H);-60~60(V)	-70~70(H);-60~65(V)(typ.)	-89~89(H); -89~89(V)	-75~75(H);-60~70(V)	-85~85(H);-85~85(V)
Synchronization Range Horizontal/Vertical	31.5~48.1KHz/56~75Hz	31.5~60.0KHz/60~75Hz	31.5~60.0KHz/60~75Hz	31.5~60.0KHz/60~75Hz	31.5~80.0KHz/56~75Hz	31.5~80.0KHz/56~75Hz
Recommended Resolution	800x600@60Hz,75Hz	1024x768@60Hz,75Hz	1024x768@60Hz,75Hz	1024x768@60Hz,75Hz	1280x1024@60Hz,75Hz	1280x1024@60Hz,75Hz
Signal Connector	15 pin D-Sub	15 pin D-Sub	15 pin D-Sub	15 pin D-sub	15 pin D-Sub	15 pin D-Sub
Power Source	AC100~240V, Universal, 10%	AC100~240V, Universal, 10%	AC100~240V, Universal, 10%	AC100~240V, Universal, 10%	AC100~240V, Universal, 10%	AC100~240V, Universal, 10%
Power Consumption	40W typical, normal operation	35W typical, normal operation	25W typical, normal operation	33W typical, normal operation	32W typical, normal operation	35W typical, normal operation
Power Management	VESA DPMS Compliant	VESA DPMS Compliant	VESA DPMS Compliant	VESA DPMS Compliant	VESA DPMS Compliant	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B	VESA DDC 1/2B	VESA DDC 1/2B	VESA DDC 1/2B	VESA DDC 1/2B	VESA DDC 1/2B
Optional Video Input	S-Video, Composite	S-Video, Composite	S-Video, Composite	S-Video, Composite	S-Video, Composite	S-Video, Composite
Optional DVI Input	No	No	Yes	Yes	Yes	Yes
Optional Touch Screen	Resistive, Capacitive, SAW,IR	Resistive, Capacitive, SAW,IR	Resistive, Capacitive, SAW,IR	Resistive, Capacitive, SAW,IR	Resistive, Capacitive, SAW,IR	Resistive, Capacitive, SAW

Industrial Computers Ltd.  
New Bury Park  
Marsh Lane  
Easthampnett  
West Sussex, PO18 0JW

Tel: +44 (0) 1243 380780  
Fax: +44 (0) 1243 538035  
eMail: sales@industrial-computers.com  
Web: www.industrial-computers.com  
Reg No: 5578804

IBUS France  
Les Espaces de Sophia  
Bâtiment K  
06 Sophia Antipolis  
France

Tel: +33 493 004 360  
Fax: +33 803 868 584  
eMail: sales@industrial-computers.com  
Web: www.industrial-computers.com

