



## Functional specifications

<b>Construction :</b>	Heavy-duty steel
<b>Drive Bay :</b>	
- External:	NB CD Drive x1 +NB FDD x1
- Internal:	3.5" HDD x2
<b>Air Filter :</b>	N/A
<b>Cooling fan :</b>	Four 4cm two ball-bearing fans
<b>Indicator :</b>	Power on/off x1, HDD x1
<b>Switch :</b>	Power on/off x1, System reset x1
<b>Speaker :</b>	N/A
<b>Connector :</b>	Two USB connectors on the front panel, reserved one COM port output
<b>Standard Colour :</b>	Black
<b>Dimension :</b>	480.4(W) x 474(D) x 44(H) mm: 19"(W) x 18.7"(D) x 1.7"(H)
<b>Weight :</b>	Net: 10Kg (22.05lb): Gross: 13kg (28.67lb)
<b>Backplane :</b>	1x PICMG 1.0 slot and 2xPCI slots

## POWER SUPPLY :

<b>Maximum Output :</b>	250W PFC
<b>Output Voltage &amp; Current :</b>	+5V-24A, +3.3V-20A, +12V-12A, -5V-0.5A, -12V-0.5A, +5Vsb-1.5A
<b>Input Voltage :</b>	90V ~ 264V AC, Full Range
<b>Input Frequency :</b>	47 ~ 63Hz
<b>Input Current :</b>	6A@115V, 3A@230V
<b>Efficiency :</b>	> 65%
<b>MTBF Reliability :</b>	105,405 hrs
<b>Certification :</b>	UL, cUL, TUV, CE, FCC
<b>ENVIRONMENT :</b>	
<b>Operating Temperature Range :</b>	0 to +40°C
<b>Storage Temperature Range :</b>	0 to +70°C
<b>Relative Humidity :</b>	5% to 95%, non-condensing

## Ordering information

ICRMPC-1UBP250 - 19" 1U rack-mount chassis with 3-slot (2xCPI) PCIMG 1.0 backplane and 250W PFC power supply

Please contact us for more information

**Website:**  
www.industrial-computers.com

**Email :**  
sales@industrial-computers.com

**Agence Ile-de-France**  
144, Avenue Paul Doumer  
78360 Montesson - France  
Téléphone : +33 (0) 130 095 950  
Télécopie : +33 (0) 139 520 318

**Industrial Computers France**  
80, route des Lucioles - B.P. 45  
06901 Sophia Antipolis Cedex - F  
Téléphone : +33 (0) 493 004 360  
Télécopie : +33 (0) 493 004 369

**Industrial Computers Ltd**  
Units 3 & 4, New Bury Park, Marsh Lane  
Easthampnett, West Sussex, PO18 0JW - UK  
Téléphone : +44 (0) 1243 380 780  
Télécopie : +44 (0) 1243 538 035

