

Aqeri 9104 is a rugged 19" 4U computer for use in harsh environments. Its small dimensions and front accessibility makes it suitable for space critical applications. The chassis is fully sealed for protection against dust and corrosive elements. Cooling is provided by a heat exchanger cooling system. A fully aluminium construction stands for low radiation and high noise immunity (according to MIL-STD-461D). The rugged design, including a separately hinged cradle for mass storage units, gives protection against shocks and vibration. An internal heating and climate control system makes the unit usable in extremely lowtemperature environments. Based on COTS technology, the computer can be configured for a various server and workstation applications. Aqeri 9104 supports Intel Pentium 4 CPU's with hyper threading technology and AGP 4X graphic controllers.

Features

- > Fully sealed all aluminium 19" 4HU chassis
- > All connectors accessible from the front
- > 28VDC power supply (18-36VDC)
- > Cooling by internal heat-exchanger system
- > Passive backplane with 2 PCI slots, 1 PCI-EX16, 2PCI-EX1
- > Mounting space for HDD, FDD, CD-ROM
- > Integrated heating and climate control system
- > EMI/RFI according to MIL-STD-461D and DEF- STAN 59-41



Specifications

Processor :	Pentium D 3.0GHz
RAM :	4GB DDR 533MHz
Operating system :	Optional
Storage :	2,5" of 3,5" HDD drive, DVD, FDD
Display interfaces:	VGA
I/O Interfaces :	2 USB 2.0, 2 Serial ports, 1 parallel, Ethernet
Expansion :	2 PCI, 1PCI-EX16, 2 PCI-EX1 Other possible uses: WLAN (2nd LAN etc), Compact flash socket (possible to boot diskless)
IR :	IrDA option
Audio :	Integrated

PHYSICAL CHARACTERISTICS

Dimensions :	440 x 177 x 450mm (WxHxD)
Weight :	15 kg
Colour :	Green

ELECTRICAL SPECIFICATIONS:

Power requirements :	28VDC (18-36VDC)
Power consumption :	175W at 28V (excluding heaters, cooler, etc)

ENVIRONMENTAL CHARACTERISTICS:

Temperature :	Operating -20°C to +55°C
Enclosure :	IP54
Vibration :	Operating 1G 10-1000Hz
Storage :	4G 10-1000Hz
Shock :	Operating: 15Gs, 11ms, 1/2 sine wave pulse

EMI/RFI/EMC According to :

MIL-STD-1275
MIL-STD-461
DEF-STAN 59-41

Designed to fulfil :

MIL-STD-461/462 C/D, MIL-STD-810, EN 61000-4-2 lev 4, EN 61000-4-3 lev 3, EN61000-4-4 lev 3, 3, EN61000-4-5 lev 1, EN61000-4-6 lev 2, EN61000- 4-8 lev 3, EN55022B, IEC 68-2-6, IEC 68-2-27, IEC68-2-29, IEC68-2-31, IEC68-2-32, DEF-STD-61-5 part 6

Please contact us for more informations

Website:
www.industrial-computers.com

Email :
sales@industrial-computers.com

Agence Ile-de-France
144, Avenue Paul Doumer
78360 Montesson - France
Téléphone : +33 (0) 130 095 950
Télécopie : +33 (0) 139 520 318

Industrial Computers France
80, route des Lucioles - B.P. 45
06901 Sophia Antipolis Cedex - F
Téléphone : +33 (0) 493 004 360
Télécopie : +33 (0) 493 004 369

Industrial Computers Ltd
Units 3 & 4, New Bury Park, Marsh Lane
Easthampnett, West Sussex, PO18 0JW - UK
Téléphone : +44 (0) 1243 380 780
Télécopie : +44 (0) 1243 538 035

