



Fonctional specifications

Construction :	Heavy-duty steel
Drive Bay :	
- External:	NB CD Drive x1 +NB FDD x1
- Internal:	3.5" HDD x2
Air Filter :	N/A
Cooling fan :	Four 4cm two ball-bearing fans
Indicator :	Power on/off x1, HDD x1
Switch :	Power on/off x1, System reset x1
Speaker :	N/A
Connector :	Two USB connectors on the front panel, reserved one COM port output
Standard Colour :	Black
Dimension :	480.4(W) x 474(D) x 44(H) mm: 19"(W) x 18.7"(D) x 1.7"(H)
Weight :	Net: 10Kg (22.05lb): Gross: 13kg (28.67lb)
Backplane :	1x PICMG 1.0 slot and 2xPCI slots

POWER SUPPLY :

Maximum Output :	250W PFC
Output Voltage & Current :	+5V-24A, +3.3V-20A, +12V-12A, -5V-0.5A, -12V-0.5A, +5Vsb-1.5A
Input Voltage :	90V ~ 264V AC, Full Range
Input Frequency :	47 ~ 63Hz
Input Current :	6A@115V, 3A@230V
Efficiency :	> 65%
MTBF Reliability :	105,405 hrs
Certification :	UL, cUL, TUV, CE, FCC
ENVIRONMENT :	
Operating Temperature Range :	0 to +40°C
Storage Temperature Range :	0 to +70°C
Relative Humidity :	5% to 95%, non-condensing

Ordering information

ICRMPC-1UBP250 - 19" 1U rack-mount chassis with 3-slot (2xCPI) PCIMG 1.0 backplane and 250W PFC power supply

Contactez-nous pour plus d'informations

Website:
www.industrial-computers.com

Email :
contact.fr@industrial-computers.com

Agence Ile-de-France
144, Avenue Paul Doumer
78360 Montesson - France
Téléphone : +33 (0) 130 095 950
Télécopie : +33 (0) 139 520 318

Industrial Computers France
80, route des Lucioles - B.P. 45
06901 Sophia Antipolis Cedex - F
Téléphone : +33 (0) 493 004 360
Télécopie : +33 (0) 493 004 369

Industrial Computers Ltd
Units 3 & 4, New Bury Park, Marsh Lane
Easthampnett, West Sussex, PO18 0JW - UK
Téléphone : +44 (0) 1243 380 780
Télécopie : +44 (0) 1243 538 035

