



### Specification

#### Dimensions

- 4U height
- 7"(H) x 17"(W) x 26"(D) 178mm(H) x 432mm(W) x 663mm(D)

#### Standard Colour Options

- Black : black crinkle [B401/P9041/6]
- Blonde : Chromadex [ICL EP 414 E]

#### Passive Backplanes

- 8 Slot ISA
  - 8 Slot ISA/PCI
  - 14 Slot ISA
  - 14 Slot ISA/PCI
  - 20 Slot ISA
  - 20 Slot PCI
- PCI-X and PCI Express Also available

#### Motherboard

- ATX form factor motherboard

#### Drive Bays

- Shock mounted drive bay
- Five 5.25"
- Support for ten front removable drives

#### Fan MTBF

- 70,000 hrs. @ 40° C

#### Cooling

- Four (4) 49.4CFM fans
- Removable front filter

#### Front Panel Controls

- Reset/ On/Off Switches
- Activity LED's

#### Ordering Information

TR4S-26C1 – 4U Rackmount front accessible drive 26" Chassis

#### Rear Panel

- AC inputs for power supplies
- DC inputs (optional)

#### Power Supplies

##### PSU2395

- Single 400W PSU(AC, 90-132/180-264Vac) (+5V @ 50A) (+12V @ 27A)(-5V @ 1A) (-12V @ 3A)

##### PSU2396

- Single 400W PSU(AC, 90-132/180-264Vac) (+5V @ 50A) (+12V @ 27A)(-5V @ 1A) (-12V @ 3A) (+3.3V @ 30A)

##### PSU2397

- Dual mini-redundant 300W ATX PSU90-132/180-264Vac(+5V @ 30A) (+12V @ 13A)(-5V @ 1A) (-12V @ 1A) (+3.3V @ 22A)
- DC Power supply optional (Call)

#### Operating Environment

- Temperature: 0 to 50° C
- Storage Temperature : -20° C-65° C
- Humidity : 5%-95% non-condensing

#### CE Approval

##### EMC directive 89/336EEC

- EN 55022 Class A
- EN 50082-1
- IEC801-2
- IEC801-3
- IEC801-4

##### LVD directive 73/23EEC

- EN 60950

- **Designed & Manufactured in the UK**
- **Customisation Service**
- **Certification Services**
- **Fully Integrated Systems**
- **Revision Controlled**