


MBU4105

Industrial Motherboard Series



MBU4105

PRODUCT HIGHLIGHTS

- ▶ Intel 6th/7th Gen Intel® Core™ with Intel® Q170
- ▶ 4 DDR4 Non-ECC DIMM up to 64GB
- ▶ Multiple expansion: 2 PCIe x16, 2 PCIe x4, 1 LPC
- ▶ 3 independent displays: VGA + DVI-I + DP++
- ▶ Rich I/O: 2 Intel GbE, 6 COM, 6 USB 3.0, 6 USB 2.0
- ▶ 15-Year CPU Life Cycle Support Until Q3' 30 (Based on Intel IOTG Roadmap)



TECHNICAL INFORMATION


SYSTEM	PROCESSOR	6 th /7 th Generation Intel® Core™/Pentium®/Celeron® LGA 1151 Socket Processors with TDP up to 95W
	CHIPSET	Intel® Q170 Chipset
	MEMORY	Four 288-pin Non-ECC DIMM up to 64GB Dual Channel DDR4 2133/2400MHz
	BIOS	Insyde SPI 128Mbit
GRAPHICS	CONTROLLER	Intel® HD Gen 9 Graphics
	FEATURE	OpenGL 5.0, DirectX 12, OpenCL 2.1 HW Decode: AVC/H.264,MPEG2,VC1/WMV9, JPEG/MJPEG, HEVC/H265, VP8, VP9 HW Encode: MPEG2, AVC/H264, JPEG, HEVC/H265, VP8, VP9
	DISPLAY	1 x VGA 1 x DVI-I (DVI-D signal) 1 x DP++ VGA: resolution up to 1920x1200 @ 60Hz DVI-I: resolution up to 1920x1200 @ 60Hz DP++: resolution up to 4096x2160 @ 60Hz
	TRIPLE DISPLAYS	VGA + DVI-I (DVI-D signal) + DP++
EXPANSION	INTERFACE	2 x PCIe x16 (Gen 3) (1 x 16 or 2 x8 signal) 2 x PCIe x4 (Gen 3)
AUDIO	AUDIO CODEC	Realtek ALC888S-VD2-GR
ETHERNET	CONTROLLER	1 x Intel® I210AT PCIe (10/100/1000Mbps) 1 x Intel® I219LM PCIe with iAMT11.0 (10/100/1000Mbps) (only Core i7/i5 supports iAMT)
REAR I/O	ETHERNET	2 x GbE (RJ-45)
	SERIAL	1 x RS-232/422/485 (RS-232 w/power (DB-9)
	USB	4 x USB 3.0 2 x USB 2.0
	PS/2	1 x PS/2 (mini-DIN-6)
	DISPLAY	1 x VGA 1 x DVI-I (DVI-D signal) 1 x DP++
	AUDIO	1 x Line-out, 1 x Mic-in, 1 x Line-in (opt., MOQ required)

► TECHNICAL INFORMATION (CONTINUED)


INTERNAL I/O	SERIAL	1 x RS-232/422/485 (RS-232 w/ power) (2.54mm pitch) 4 x RS-232 (2.54mm pitch)
	USB	4 x USB 3.0 (2.00mm pitch) 2 x USB 2.0 (2.54mm pitch)
	AUDIO	1 x Audio (Line-out/MIC-in) (opt., MOQ required) 1 x S/PDIF
	SATA	6 x SATA 3.0 RAID 0/1/5/10
	DIO	1 x 8-bit DIO
	LPC	1 x LPC (supports LPC EXT-RS232/RS485 module)
	SMBUS	1 x SMBus
	OUTPUT & INTERVAL	System Reset, Programmable via Software from 1 to 255 Seconds
	SECURITY TPM	Opt., MOQ required
	TYPE	ATX
	CONNECTOR	8-pin ATX 12V power 24-pin ATX power
	CONSUMPTION	TBD
	RTC BATTERY	CR2032 Coin Cell
OS SUPPORT		Windows 10 64-bit Windows 7 32/64-bit Windows 8.1 64-bit Linux (Note: 7 th Gen CPUs only support Windows 10 64-bit & Linux)
ENVIRONMENT	TEMPERATURE	Operating: 0 to 60°C Storage: -30 to 60°C with RTC Battery, -40 to 85°C without RTC Battery
	HUMIDITY	Operating: 5 to 90% RH Storage: 5 to 90% RH
	MTBF	374,618 hrs @ 25°C; 211,926 hrs @ 45°C; 133,291 hrs @ 60°C Calculation Model: Telcordia Issue 2, Method Case 3 Environment: GB, GC – Ground Benign, Controlled
MECHANICAL	DIMENSIONS	microATX Form Factor 244mm (9.6") x 244mm (9.6")
	HEIGHT	PCB: 1.6mm Top Side: 38.5mm Bottom Side: 4.40mm
CERTIFICATIONS		CE, FCC, RoHS, UL

MBU4105


MECHANICAL DRAWING



BLOCK DIAGRAM



MOTHERBOARD LAYOUT



Company Address

Kontron UK Limited
Units 3, 4, 5, 9 & 10 New Bury Park
Marsh Lane, Easthamptnett, UK
TEL: +44 (0) 1243 380780
uksales@kontron.com
www.industrial-computers.com