


PPC2018

Industrial Panel PC Series



PPC2018

PRODUCT HIGHLIGHTS

- ▶ 10.4" XGA TFT LCD display with LED backlight
- ▶ Fanless cooling system with Intel® Celeron® processor N3060
- ▶ 2 GbE LAN, 4 USB and 2 COM
- ▶ Easy access storage design
- ▶ Supports optional panel mount/wall mount/desktop stand
- ▶ Supports RFID (optional)
- ▶ Plastic and IP65-rated front bezel




TECHNICAL INFORMATION

PANEL	10.4" XGA/SVGA TFT LCD with LED backlight 350 nits (XGA) 400 nits (SVGA) 1024 x 768 (XGA) 800 x 600 (SVGA)
PROCESSOR	Intel® Celeron® processor N3060 (up to 2.48 GHz)
CHIPSET	SoC integrated
SYSTEM MEMORY	1 x 204-pin DDR3L-1600 SO-DIMM, up to 8GB
BIOS	AMI
COM	1 x RS-232 1 x RS-232/422/485
USB	2 x USB 2.0 2 x USB 3.0
ETHERNET	2 x 10/100/1000 Mbps (Intel® i211-AT)
DISPLAY	1 x HDMI
AUDIO	1 x Audio (Line-out)
STORAGE	1 x 2.5" SATA HDD (9.5 mm height) 1 x mSATA
EXPANSION	1 x Full-size PCI Express Mini Card slot with mSATA 1 x Full-size PCI Express Mini Card slot with SIM
OTHERS	1 x Switch for power On/Off 1 x AT/ATX mode selection switch
TOUCHSCREEN	5-wire resistive touch
FRONT BEZEL	IP65, NEMA 4 rugged protection, plastic front bezel
POWER SUPPLY	AC version: 100 - 240VAC-DC, 60W power adapter or DC version: 24 VDC with over current protection fuse
POWER CONSUMPTION	32W
WATCHDOG TIMER	255 levels, 0 to 255 sec.
OPERATING TEMPERATURE	0°C to +50°C (+32°F to +122°F) (with W.T. DRAM/HDD in airflow condition) 0°C to +45°C (+32°F to +113°F) (with W.T. DRAM/HDD)
RELATIVE HUMIDITY	20% to 90% @ 40°C; non-condensing
VIBRATION	2G, 5 - 500Hz, random for SSD
DIMENSIONS (W X D X H)	292.5 x 45.8 x 235.8 mm (11.52" x 1.80" x 9.28")
WEIGHT (NET/GROSS)	1.8 kg (3.96 lb)/3 kg (6.61 lb)
CERTIFICATIONS	CE, FCC, UL60950-1
OS SUPPORT	WES 7, Windows® 7, WE8S (64-bit), Windows® 8.1 (64-bit), Windows® 10
MOUNTING	Panel mount Wall mount VESA arm Desktop stand

► TECHNICAL INFORMATION (CONTINUED)

PART NUMBERS	PPC2018: 10.4" SVGA fanless touch panel computer with Intel® Celeron® processor N3060, 5-wire resistive touch screen, AC-DC 60W power adapter (screw type connector) and EMI class A PPC2018-01: 10.4" SVGA fanless touch panel computer with Intel® Celeron® processor N3060, 5-wire resistive touch screen and 24 VDC power input (terminal block connector) PPC2018-02: 10.4" XGA fanless touch panel computer with Intel® Celeron® processor N3060, 5-wire resistive touch screen, AC-DC 60W power adapter (screw type connector) and EMI class A PPC2018-03: 10.4" XGA fanless touch panel computer with Intel® Celeron® processor N3060, 5-wire resistive touch screen and 24 VDC power input (terminal block connector)
OPTIONS	Wi-Fi + Bluetooth kit Speaker kit Panel mount kit VESA mount kit Stand kit RFID kit

► MECHANICAL DRAWING



► Company Address

Kontron UK Limited
 Units 3, 4, 5, 9 & 10 New Bury Park
 Marsh Lane, Easthampnett, UK
 TEL: +44 (0) 1243 380780
uksales@kontron.com
www.industrial-computers.com