

ICOM2495

Industrial 2U Rackmount 6th/7th Gen & Xeon System



ICOM2495

PRODUCT HIGHLIGHTS

- ▶ 2U 19" 20.80" Deep Rackmount system with 7 x low profile expansion slots
- ▶ Life Cycle Support Until Q2 2025
- ▶ Industrial motherboard based solution
- ▶ Supports Intel 6th/7th Gen Intel® Xeon®/Core™ with Intel® C236 chipset
- ▶ 4 DDR4 ECC/Non-ECC UDIMM up to 64GB
- ▶ Motherboard expansion slots: 2 PCIe x16, 3 PCIe x4, 2 PCI, 1 x M.2
- ▶ Rich I/O: 2 Intel GbE, 6 COM, 6 USB 3.1, 7 USB 2.0
- ▶ Supports 3 independent displays




TECHNICAL INFORMATION

PROCESSOR	6 th /7 th Generation Intel® Xeon®/Core™/Pentium®/Celeron® LGA 1151 Socket Processors with TDP up to 95W
CHIPSET	Intel® C236 Chipset
MEMORY	Four 288-pin ECC/Non-ECC UDIMM up to 64GB Dual Channel DDR4 2133/2400MHz (Core™ i5/i7 only support non-ECC)
BIOS	Insyde SPI 128Mbit
STORAGE	Supports 2 x 5.25" SATA drive bays & 2 x 3.5" drive bays Supports 5 x SATA3.0, (1 SATA shared with mini PCIe (SATA), default at mini PCIe/2 SATA shared with M.2, default at M.2), RAID 0/1/5/10 Optional removable hard disk drives or solid state disks
OPTICAL	DVD±RW (±R DL) / DVD-RAM drive
WATCHDOG TIMER	Programmable via S/W from 1 sec. to 255 sec.
EXPANSION SLOTS	Chassis supports 7 x low profile chassis expansion slots Motherboard expansion slots: 2 x PCIe x16 (1 x16 or 2 x8 signal) (Gen 3), 3 x PCIe x4 (Gen 3) 2 x PCI 1 x M.2 2260/2280 M key (SATA3.0/PCIe Gen3 x 2 NVMe) 1 x Mini PCIe (PCIe/mSATA/USB 2.0) 1 x PCIe x16 (Gen 3), 6 x PCI
POWER SUPPLY OPTIONS	400W ~ 600W 90~250VAC DC 12~48V Redundant Power Supplies
AUDIO	Realtek ALC888S-VD2-GR
ETHERNET	1 x Intel® I211AT PCIe (10/100/1000Mbps) 1 x Intel® I219V PCIe (10/100/1000Mbps)
OPERATING SYSTEMS SUPPORTED	Windows 10 64-bit Windows 7 32/64-bit Windows 8.1 64-bit Linux (Note: 7 th Gen CPUs only support Windows 10 64-bit & Linux)
DISPLAY	1 x VGA 1 x DVI-I (DVI-D signal) 1 x DP++ VGA: resolution up to 1920x1200 @ 60Hz DVI-D: resolution up to 1920x1200 @ 60Hz DP++: resolution up to 4096x2160 @ 60Hz
MULTI-DISPLAY OUTPUTS	Supports Triple Displays: VGA + DVI-I (DVI-D signal) + DP++
REAR I/O PORTS	2 x GbE (RJ-45) 1 x RS-232/422/485 (RS-232 w/power (DB-9) 4 x USB 3.1 & 2 x USB 2.0 1 x PS/2 (mini-DIN-6) 1 x VGA 1 x DVI-I (DVI-D signal) 1 x DP++ 1 x Line-out, 1 x Mic-in, 1 x Line-in (opt., MOQ required)


► TECHNICAL INFORMATION (CONTINUED)

OPTIONAL PORT EXPANSION FROM MOTHERBOARD	1 x RS-232/422/485 (RS-232 w/ power) (2.54mm pitch) 4 x RS-232 (2.54mm pitch) 2 x USB 3.1 Gen1 4 x USB 2.0 + 1 x Vertical USB 2.0 (type A)
FRONT CHASSIS CONNECTORS	2 x USB
DRIVE BAYS	2 x 5.25" SATA 2 x 3.5" drive bays
MOTHERBOARD MTBF	537,588 hrs @ 25°C; 298,813 hrs @ 45°C; 184,762 hrs @ 60°C Calculation model: Telcordia Issue 4 Environment: GB, GC – Ground Benign, Controlled
ENVIRONMENT	Operating: 0 to 60°C Storage: -30 to 60°C with RTC Battery; -40 to 85°C without RTC Battery
COOLING	2x replaceable air filters 1x 8cm cooling fan 3x 6cm optional cooling fans
COLOUR	Black (all other optional colours are available upon request)
DIMENSIONS:	482.6 (W) x 528.3 (D) x 88.9 (H); 19" (W) x 20.8 (D) x 3.5" (H)

► MECHANICAL DRAWING



► MOTHERBOARD DETAILS



► Company Address

Kontron UK Limited
Units 3, 4, 5, 9 & 10 New Bury Park
Marsh Lane, Easthampnett, UK
TEL: +44 (0) 1243 380780
uksales@kontron.com
www.industrial-computers.com