

ICOM2498

Industrial 2U Rackmount 10th Gen System



ICOM2498

PRODUCT HIGHLIGHTS

- ▶ 2U 19" 20.80" Deep Rackmount system with 7 x low profile expansion slots
- ▶ Life Cycle Support Until Q2' 34
- ▶ Industrial motherboard based solution
- ▶ Supports Intel 10th Gen Intel® Core Processors with H420E chipset
- ▶ 2 DDR4 UDIMM up to 64GB
- ▶ Motherboard expansion slots: 1 PCIe x16, 1 PCIe x4, 5 PCI, 1 x M.2
- ▶ Rich I/O: 2 Intel GbE, 6 COM, 10 USB
- ▶ Supports 2 independent displays




TECHNICAL INFORMATION

PROCESSOR	10th Generation Intel® LGA 1200 Socket Processors, TDP support up to 125W Intel® Core™ i9-10900E (10 Cores, 20M Cache, up to 4.7 GHz); 65W Intel® Core™ i9-10900TE (10 Cores, 20M Cache, up to 4.5 GHz); 35W Intel® Core™ i7-10700E (8 Cores, 16M Cache, up to 4.5 GHz); 65W Intel® Core™ i7-10700TE (8 Cores, 16M Cache, up to 4.4 GHz); 35W Intel® Core™ i5-10500E (6 Cores, 12M Cache, up to 4.2 GHz); 65W Intel® Core™ i5-10500TE (6 Cores, 12M Cache, up to 3.7 GHz); 35W Intel® Core™ i3-10100E (4 Cores, 6M Cache, 3.8 GHz); 65W Intel® Core™ i3-10100TE (4 Cores, 6M Cache, to 3.6 GHz); 35W Intel® Pentium® G6400E (2 Cores, 4M Cache, 3.8 GHz); 58W Intel® Pentium® G6400TE (2 Cores, 4M Cache, 3.2 GHz); 35W Intel® Celeron® G5900E (2 Cores, 2M Cache, 3.2 GHz); 58W Intel® Celeron® G5900TE (2 Cores, 2M Cache, 3.0 GHz); 35W
CHIPSET	Intel® H420E Chipset
MEMORY	Two 288-pin up to 128GB Dual Channel DDR4 2400/2666/2933MHz
BIOS	AMI SPI 128Mbit
STORAGE	Supports 2 x 5.25" SATA drive bays & 2 x 3.5" drive bays Supports 4 x SATA3.0 Optional removable hard disk drives or solid state disks
OPTICAL	DVD±RW (±R DL) / DVD-RAM drive
WATCHDOG TIMER	Programmable via S/W from 1 sec. to 255 sec.
EXPANSION SLOTS	Chassis supports 7 x low profile chassis expansion slots Motherboard expansion slots: 1 x PCIe x16 (Gen 3), 1 x PCIe x4 (Gen 3), 5 x PCI 1 x M.2 M Key (PCIe x4 NVMe share with PCIe x4 slot, opt., MOQ required)
POWER SUPPLY OPTIONS	400W ~ 600W 90~250VAC DC 12~48V Redundant Power Supplies
AUDIO	Realtek ALC888S-VD2-GR
ETHERNET	1 x Intel® I211AT PCIe (10/100/1000Mbps) 1 x Intel® I219LM/I219V with iAMT12.0 (10/100/1000Mbps)
OPERATING SYSTEMS SUPPORTED	Windows 10 IoT Enterprise 64-bit Linux Ubuntu 20.04
DISPLAY	1 x VGA, 1 x DP++ 1 x HDMI 1.4b VGA resolution up to 1920x1200 @ 60Hz DP++ resolution up to 4096x2160 @ 60Hz HDMI: resolution up to 4096x2160 @ 24Hz
MULTI-DISPLAY OUTPUTS	Supports Dual Displays: VGA + DP++ VGA + HDMI DP++ + HDMI


TECHNICAL INFORMATION (CONTINUED)

REAR I/O PORTS	2 x GbE (RJ-45) 1 x RS-232/422/485 (RS-232 w/power (DB-9) 4 x USB 3.2 Gen 1 2 x USB 2.0 1 x PS/2 (mini-DIN-6) 1 x VGA 1 x DP++ 1 HDMI 1 x Line-out, 1 x Mic-in, 1 x Line-in (opt., MOQ required)
OPTIONAL PORT EXPANSION FROM MOTHERBOARD	1 x RS-232/422/485 (RS-232 w/ power) (2.54mm pitch) 4 x RS-232 (2.54mm pitch) 2 x USB 3.2 Gen 1 2 x USB 2.0 (2.54mm pitch, Colay vertical Type A, opt.: MOQ required)
FRONT CHASSIS CONNECTORS	2 x USB
DRIVE BAYS	2x 5.25" SATA & 2 x 3.5" drive bays
MOTHERBOARD MTBF	521,024 hrs @ 25°C ; 292,119 hrs @ 45°C ; 181,960 hrs @ 60°C ; 155,038 hrs @ 65°C Calculation Model: Telcordia Issue 4 Environment: GB, GC - Ground Benign, Controlled
ENVIRONMENT	Operating: 0 to 60°C Storage: -30 to 60°C with RTC Battery; -40 to 85°C without RTC Battery
COOLING	2x replaceable air filters 1x 8cm cooling fan 3x 6cm optional cooling fans
COLOUR	Black (all other optional colours are available upon request)
DIMENSIONS:	482.6 (W) x 528.3 (D) x 88.9 (H); 19" (W) x 20.8 (D) x 3.5" (H)

MECHANICAL DRAWING



MOTHERBOARD DETAILS



Company Address

Kontron UK Limited
 Units 3, 4, 5, 9 & 10 New Bury Park
 Marsh Lane, Easthampnett, UK
 TEL: +44 (0) 1243 380780
uksales@kontron.com
www.industrial-computers.com