

ICOM724

Industrial mATX Wallmount/Desktop 6th/7th Gen System



ICOM724

PRODUCT HIGHLIGHTS

- ▶ Wallmount/Desktop mATX motherboard system
- ▶ Intel 6th/7th Gen Intel® Core™ with Intel® H110
- ▶ 2 DDR4 DIMM up to 32GB
- ▶ Multiple expansion: 4 PCI
- ▶ 3 independent displays: VGA+DVI-I+DP++
- ▶ Rich I/O: 2 Intel GbE, 6 COM, 4 USB 3.0, 6 USB 2.0
- ▶ 15-Year CPU Life Cycle Support Until Q1 '32 (Based on Intel IOTG Roadmap)
- ▶ 1 x 5.25" and 2 x internal 3.5" drive bays




TECHNICAL INFORMATION

PROCESSOR	7th Gen Intel® Core™/Pentium®/Celeron® LGA 1151 Processors TDP up to 95W: Intel® Core™ i7-7700K (4 Cores, 8M Cache, up to 4.5 GHz); 91W (Non-LTS) Intel® Core™ i7-7700 (4 Cores, 8M Cache, up to 4.2 GHz); 65W Intel® Core™ i7-7700T (4 Cores, 8M Cache, up to 3.8 GHz); 35W Intel® Core™ i5-7500 (4 Cores, 6M Cache, up to 3.8 GHz); 65W Intel® Core™ i5-7500T (4 Cores, 6M Cache, up to 3.3 GHz); 35W Intel® Core™ i3-7101E (2 Cores, 3M Cache, 3.9 GHz); 65W Intel® Core™ i3-7101TE (2 Cores, 3M Cache, to 3.4 GHz); 35W 6th Gen Intel® Core™/Pentium®/Celeron® LGA 1151 Processors TDP up to 95W: Intel® Core™ i7-6700K (Cores, 8M Cache, up to 4.2 GHz); 91W (Non-LTS) Intel® Core™ i7-6700 (4 Cores, 8M Cache, up to 4.0 GHz); 65W Intel® Core™ i7-6700TE (4 Cores, 8M Cache, up to 3.4 GHz); 35W Intel® Core™ i5-6500 (4 Cores, 6M Cache, up to 3.6 GHz); 65W Intel® Core™ i5-6500TE (4 Cores, 6M Cache, up to 3.3 GHz); 35W Intel® Core™ i3-6101E (2 Cores, 4M Cache, 3.7 GHz); 65W Intel® Core™ i3-6101TE (2 Cores, 4M Cache, to 2.7 GHz); 35W Intel® Pentium® G4400 (2 Cores, 3M Cache, 3.3 GHz); 65W Intel® Pentium® G400TE (2 Cores, 3M Cache, 2.9 GHz); 35W Intel® Celeron® G3900 (2 Cores, 2M Cache, 2.8 GHz); 65W Intel® Celeron® G3900TE (2 Cores, 2M Cache, 2.6 GHz); 35W
CHIPSET	Intel® H110 Chipset
MEMORY	Two 288-pin DIMM up to 64GB, Dual Channel DDR4 2133/2400MHz
BIOS	Insyde SPI 128Mbit
STORAGE	1x external 5.25" & 2x internal 3.5" drive bays Supports 4 x SATA 3.0 & Supports RAID 0/1/5/10 Optional removable hard disk drives or solid state disks
OPTICAL	DVD±RW (±R DL) / DVD-RAM drive
WATCHDOG TIMER	Programmable via S/W from 1 sec. to 255 sec.
EXPANSION SLOTS	4 x PCI
POWER SUPPLY	400w SFX Industrial 100,000 MTBF power supply
AUDIO	Realtek ALC888S-VD2-GR
ETHERNET	1 x Intel® I211AT PCIe (10/100/1000Mbps) 1 x Intel® I219V PCIe (10/100/1000Mbps)
OPERATING SYSTEMS SUPPORTED	Windows 7 32/64-bit & Window 8.1 64-bit & Windows 10 64-bit Linux (Note: 7th Gen CPU SKU ONLY support Windows 10 64-bit & Linux)
DISPLAY	1 x VGA: resolution up to 1920x1200 @ 60Hz 1 x DVI-I (DVI-D signal) : resolution up to 1920x1200 @ 60Hz 1 x DP++ resolution up to 4096x2160 @ 60Hz
MULTI-DISPLAY OUTPUTS	Supports Triple Displays: VGA + DVI-D + DP++
REAR I/O PORTS	2 x GbE (RJ-45) 1 x RS-232/422/485 (RS-232 w/power (DB-9) 4 x USB 3.0 & 2 x USB 2.0 1 x PS/2 (mini-DIN-6) 1 x VGA, 1 x DVI-I (DVI-D signal), 1 x DP++ 1 x Line-out, 1 x Mic-in, 1 x Line-in (opt., MOQ required)


► TECHNICAL INFORMATION (CONTINUED)

OPTIONAL PORT EXPANSION FROM MOTHERBOARD	1 x RS-232/422/485 (RS-232 w/ power) (2.54mm pitch) 4 x RS-232 (default), 4 x RS-232 (available upon request – MOQ required) 4 x USB 2.0 (2.54mm pitch)
FRONT CHASSIS CONNECTORS	2 x USB ports on front panel
CHASSIS CONSTRUCTION	Heavy-duty Steel 3mm aluminium front panel
DRIVE BAYS	1x external 5.25" 2x internal 3.5" drive bays
SWITCHES	Power On/Off
INDICATORS	Power On/Off HDD activity
MOTHERBOARD MTBF	527,696 hrs @ 25°C; 296,924 hrs @ 45°C ; 184,794 hrs @ 60°C Calculation Model: Telcordia Issue 4 Environment: GB, GC - Ground Benign, Controlled
ENVIRONMENT	Operating: 0 to 60°C Storage: -30 to 60°C with RTC Battery; -40 to 85°C without RTC Battery
COOLING	8cm ball-bearing fan
COLOUR	Black (all other optional colours are available upon request)
DIMENSIONS:	337 x 339.8 x 136 mm (13.26 x 13.4 x 5.36 inches)

► MECHANICAL DRAWING



► MOTHERBOARD DETAILS



► Company Address

Kontron UK Limited
Units 3, 4, 5, 9 & 10 New Bury Park
Marsh Lane, Easthampnett, UK
TEL: +44 (0) 1243 380780
uksales@kontron.com
www.industrial-computers.com