

ICOM471

Industrial 4U Rackmount 10th Gen System



ICOM471

PRODUCT HIGHLIGHTS



- ▶ 4U 19" 13.7" Shallow depth Rackmount system
- ▶ Life Cycle Support Until Q2' 34
- ▶ Industrial motherboard based solution, Intel® H420E Chipset
- ▶ Supports Intel® 10th Generation Core™ / Pentium® / Celeron LGA 1151 Socket Processors
- ▶ 2 DDR4 UDIMM up to 64GB
- ▶ Expansion for 1 PCIe x16, 1 PCIe x4, 5 PCI
- ▶ Rich I/O: 2 Intel GbE, 6 COM, 10 USB
- ▶ Front to back cooling with three system fans



TECHNICAL INFORMATION

PROCESSOR	10th Generation Intel® LGA 1200 Socket Processors, TDP support up to 125W Intel® Core™ i9-10900E (10 Cores, 20M Cache, up to 4.7 GHz); 65W Intel® Core™ i9-10900TE (10 Cores, 20M Cache, up to 4.5 GHz); 35W Intel® Core™ i7-10700E (8 Cores, 16M Cache, up to 4.5 GHz); 65W Intel® Core™ i7-10700TE (8 Cores, 16M Cache, up to 4.4 GHz); 35W Intel® Core™ i5-10500E (6 Cores, 12M Cache, up to 4.2 GHz); 65W Intel® Core™ i5-10500TE (6 Cores, 12M Cache, up to 3.7 GHz); 35W Intel® Core™ i3-10100E (4 Cores, 6M Cache, 3.8 GHz); 65W Intel® Core™ i3-10100TE (4 Cores, 6M Cache, to 3.6 GHz); 35W Intel® Pentium® G6400E (2 Cores, 4M Cache, 3.8 GHz); 58W Intel® Pentium® G6400TE (2 Cores, 4M Cache, 3.2 GHz); 35W Intel® Celeron® G5900E (2 Cores, 2M Cache, 3.2 GHz); 58W Intel® Celeron® G5900TE (2 Cores, 2M Cache, 3.0 GHz); 35W
CHIPSET	Intel® H420E Chipset
MEMORY	Two 288-pin up to 64GB Dual Channel DDR4 2400/2666/2933MHz
BIOS	SPI 256Mbit
STORAGE	Supports 1x Slimline 5.25" drive bay & 3x 3.5" drive bays Supports 4 x SATA3.0 Optional removable hard disk drives or solid state disks
OPTICAL	Optional Slimline DVD±RW (±R DL) / DVD-RAM drive
WATCHDOG TIMER	Programmable via S/W from 1 sec. to 255 sec.
EXPANSION SLOTS	1 x PCIe x16 (Gen 3) 1 x PCIe x4 (Gen 3) 5 x PCI 1 x M.2 M Key (PCIe x4 NVMe share with PCIe x4 slot, opt., MOQ required)
POWER SUPPLY OPTIONS	400W ~ 600W 90~250VAC
AUDIO	Realtek ALC888
ETHERNET	1 x Intel® I211AT PCIe (10/100/1000Mbps) 1 x Intel® I219LM/I219V with iAMT12.0 (10/100/1000Mbps)
OPERATING SYSTEMS SUPPORTED	Windows 10 Pro 64-bit Windows 10 IoT Enterprise 64-bit Linux
DISPLAY	1 x VGA, 1 x DP++ 1 x HDMI 1.4b VGA resolution up to 1920x1200 @ 60Hz DP++ resolution up to 4096x2160 @ 60Hz HDMI: resolution up to 4096x2160 @ 24Hz
MULTI-DISPLAY OUTPUTS	Supports Dual Displays: VGA + DP++ VGA + HDMI DP++ + HDMI

REAR I/O PORTS	2 x GbE (RJ-45) 1 x RS-232/422/485 (RS-232 w/power (DB-9) 4 x USB 3.2 Gen 1 2 x USB 2.0 1 x PS/2 mini-DIN-6 1 x VGA 1 x DP++ 1 HDMI 1 x Line-out, 1 x Mic-in, 1 x Line-in (opt., MOQ required)
OPTIONAL PORT EXPANSION FROM MOTHERBOARD	1 x RS-232/422/485 (RS-232 w/ power) (2.54mm pitch) 4 x RS-232 (2.54mm pitch) 2 x USB 3.2 Gen 1 2 x USB 2.0 (2.54mm pitch, Colay vertical Type A, opt.: MOQ required)
FRONT CHASSIS CONNECTORS	2 x USB
DRIVE BAYS	1x Slimline 5.25" drive bay 2x 3.5" external & 1 x 3.5" internal drive bays
MOTHERBOARD MTBF	521,024 hrs @ 25°C ; 292,119 hrs @ 45°C ; 181,960 hrs @ 60°C ; 155,038 hrs @ 65°C Calculation Model: Telcordia Issue 4 Environment: GB, GC - Ground Benign, Controlled
ENVIRONMENT	Operation Temperature: 0 °C to +50 °C continuous operation Storage Temperature: -20 °C to +70 °C Humidity: 10 % to 93 % @40 °C, non-condensing (Dependent on overall system specification)
VIBRATION	Operating: 10-150 Hz: 1G/3 axis Non-operating: 10-150 Hz: 2G/3 axis
COOLING	Removable air filter 2x80mm & 1x120mm
COLOUR	Black (all other optional colours are available upon request)
DIMENSIONS:	482.6 x 177.8 x 348.0 mm / 19.00" x 7.00" x 13.70") (W x H x D)



Kontron UK Limited
Units 3, 4, 5, 9 & 10 New Bury Park
Marsh Lane, Easthampnett, UK
TEL: +44 (0) 1243 380780
uksales@kontron.com
www.industrial-computers.com